



PN-TX-MX8B

| Transmitter PN-TX-MX8B                      |   |
|---|---|
| <b>Article no.</b>                          | PN-T19-2                                  |
| <b>Frequency</b>                            | 2,4 GHz , 16 channels                     |
| <b>Mod.type</b>                             | FM-Modulation, narrow band                |
| <b>Code comb.</b>                           | 16.777.216                                |
| <b>Radio type</b>                           | DSSS                                      |
| <b>Output</b>                               | 5 mW (by 50 ohm)                          |
| <b>Buttons</b>                              | 8 x 2 -step buttons                       |
| <b>No. of batteries</b>                     | 3   |
| <b>Battery</b>                              | Exchangeable                              |
| <b>Type of batteries</b>                    | AAA/LR03                                  |
| <b>Operating time with continuous usage</b> | 200 h                                     |
| <b>Weight</b>                               | ~ 331 g / ~ 0.7 lb                        |
| <b>Dimensions</b>                           | ~ 80 x 185 x 44 mm / ~ 3.1 x 7.3 x 1.7 in |
| <b>Protection</b>                           | IP65                                      |
| <b>Temperature</b>                          | -20 to +55 °C / -4 to +130 F              |
| <b>Safety level</b>                         | CAT3, PLd                                 |
| <b>On/off switch</b>                        | Yes                                       |

The product picture above is for illustrative purposes only, actual product appearance might be slightly different.



PN-RX-MDB10

| Receiver PN-RX-MDB10          |  |
|-------------------------------|--|
| <b>Article no.</b>            | PN-R15-2                                 |
| <b>Frequency</b>              | 2,4 GHz , 16 channels                    |
| <b>No. of function relays</b> | 10   8A, 250V AC                         |
| <b>No. of stop relays</b>     | 2  |
| <b>Duplex</b>                 | No                                       |
| <b>Power supply</b>           | 230V AC & 48V AC & 115V AC               |
| <b>Dimensions</b>             | ~ 120 x 116 x 50 mm / ~ 4.7 x 4.6 x 2 in |
| <b>Protection</b>             | IP66                                     |
| <b>Safety level</b>           | CAT3, PLd                                |
| <b>Radio type</b>             | PLL Synthesizer                          |
| <b>Bus system</b>             | None                                     |
| <b>Temperature</b>            | -20 to +55 °C / -4 to +130 F             |

The product picture above is for illustrative purposes only, actual product appearance might be slightly different.